

SSP-313-F SPECIFICATIONS

HANDSET TELEPHONE PANEL WITH KEYPAD & SMART FEATURES

Standard Analog Power, but also available in VoIP versions

Durable stainless steel flush mount panel telephone for dialing with call restrictions. Programmable prefix or access dialing capability, call time duration setting from no limit up to 30 minutes, allow or block incoming calls, and 40 (1-11 digits) programmable speed dialing locations or speed dial only software. Equipped with marine quality chrome tone dial keypad and mechanical hookswitch, ID window or optional (-IVC) pushbutton volume control with background noise reduction, and 32" hearing aid compatible armored cord handset. Telephone can be flush mounted or installed in our 331-005 weatherproof or 331-HOB weather resistant housing.



SPECIFICATIONS

Panel Size:	7 1/6"W x 11 1/4"H 2"D (Behind Panel) 3"D (Front Panel & Handset on Hook)
Weight:	Approximately 6 lbs.
Mounting Instructions:	Flush Mounted Weatherproof Housing (WPP) Weather Resistant Open Enclosure (HOB)
Environment:	Temperature: -30°C (-22°F) to 60°C (140°F) Humidity: 0%-90% non-condensating
Input Power:	Telephone Line Powered
Programming:	VIA DTMF keypad
Loop Current:	25mA min to 80ma max (48 Volt Loop)
Impedance:	600 ohms
Type Jack:	RJ11C
Ringer Equivalency:	0.4A
Hearing Aid Compatible:	Meets EIA standards
UL & FCC Registration:	Certified
ACCESSORIES:	301-064 Security Tool (only required for installation when in HOB or WPP)



ADDITIONAL OPTIONS IP - Voice over Internet Protocol Version available on all models (SIP)

-M	-IVC	-CCH*	-LB	Open Enclosure Housing	Weatherproof Housing	-RIL
Sealed Magnetic Hookswitch • Completely Sealed • No Moving Parts	Internal Volume Control • Push Button Volume Control • Background Noise reduction	Coiled cord available from 5', 10', & 15' (feet). Example: -CCH5 5' Long	Handset w/ internal steel lanyard (braided metal rope) and lanyard mounting bracket that is secured onto panel for added strength.	Standard Black Housing -R Red Housing -S Stainless Steel Housing	Standard Black & TELEPHONE on Door • -B-EMER Black & EMERGENCY on Door • -R Red & EMERGENCY on Door • -R-TEL Red & TELEPHONE on Door • -Y Yellow & EMERGENCY on Door • -Y-TEL Yellow & Telephone on Door • -G Grey & TELEPHONE on Door • -G-EMER Grey & EMERGENCY on Door	Ring Indicator Light located on the phone panel for visual ring indication.



Providing Telecommunication Solutions Since 1930

Communication Equipment

519 SW Park Street

& Engineering Company

Okeechobee, FL

<http://www.ceeco.net>

Voice 863-357-0798

Email: sales@ceeco.net

Fax 863-357-0006