

SSP-511 SPEAKERPHONES

Stainless Steel, Vandal Resistant, Rugged Speakerphone Panels Built to Last

The CEECO Model SSP-511 vandal resistant, stainless steel speakerphones offer clear, reliable communication. Our handsfree phones are available with keypad (-F), autodial (-D), and ring-down (-X) operation. The rugged SSP speakerphones are suitable for courtesy, emergency, and entrance security communication. The speakerphone operation is a press to start, press to stop call button for the initiation and termination of phone calls with an LED visual call process indication light. Call restrictions, ADA, and speed dial features are available. These panels fit in both the WPP (weatherproof) and HOB (open enclosure) housing or can be flush mounted into a customer's designed mounting.

- Allow or block incoming calls
- Automatically dial a PBX or access number
- Resets after call party disconnects, cannot be left off-hook.
- Call restriction features programmable
- Time calls at different time increments
- Muted microphone during dial tone to eliminate fraud attempts



Made in the USA 

SPECIFICATIONS

POWER:	C.O. Line powered
LOOP CURRENT:	30mA min. to 80mA max.
LOOP CURRENT:	27mA min. to 80mA max. (low power)
IMPEDANCE:	600 ohms
SIGNALING:	DTMF, 70ms tone, 50ms spacing
SIGNALING:	Manual on-off Hook (for 511-X)
OUTPUT:	-4.0dbm to -6.0dbm
ENVIRONMENTAL:	Temp: -30°C (-22°F) to 60°C (140°F) Humidity 0% to 90% non-condensating
PROGRAMMING:	Via DTMF keypad.
DIMENSIONS:	7 1/6"W X 11 1/4" H X 4 1/4"D
MOUNTING:	Vertical surface mount
MEMORY RETENTION:	Non-volatile memory retention
WEIGHT:	Approximately 6 Pounds
TYPE JACK:	RJ11C

ACCESSORIES:

301-064 Security Tool (required for installation)



FEATURES

7 1/6"W x 11 1/4"H x 4 1/4"D

Weight 6 lbs

Tamper Resistant Security Hardware

Puncture and Weather Proof Speaker

Low Powered versions available

Optional ADA features available

Optional 2nd Number Autodial -D2

Can be mounted in an HOB (Open enclosure) or a WPP (Weatherproof) Housing

Line Powered

Requires 301-064 Security Tool for Installation

1 Year Warranty and Lifetime Support



Providing Telecommunication Solutions Since 1930

Communication Equipment
& Engineering Company

Web: www.ceeco.net

Email: sales@ceeco.net

519 SW Park Street
Okeechobee, FL 34972

Voice 863-357-0798

Fax 863-357-0006

SSP-511 SPEAKERPHONES

PRODUCT MANUALS WITH FULL FEATURES AND FUNCTIONS AVAILABLE UPON REQUEST

			
<u>SSP-511-F</u>	<u>SSP-511-FD-ADA</u>	<u>SSP-511-DD-ADA</u>	<u>SSP-511-D, SSP-511-D2</u> <u>SSP-511-X</u>
The SSP-511-F speakerphone with keypad provides DTMF dialing. Phone can be programmed for call restrictions and blocking, speed dial, conversation time-out, and PBX prefix dialing. Stainless steel design with puncture and weatherproof speaker, metal keypad, and security screw installation make this phone ideal for your toughest environments.	The SSP-511-FD Telephone (SSP-511-FD-ADA shown above) provides call restriction capabilities to include call blocking. For example: block 1+ calling, can be programmed to dial an access code, allow or block incoming calls, provide separate conversation timers or no timed call for both autodial and keypad from 1-9 minutes, and adjustable wink detect length if necessary.	The SSP-511-DD-ADA (shown with optional –ADA feature) stainless steel speakerphone is equipped with Braille 'EMER' emergency plate and LED indicator light that changes color to show call progress. The SSP-511-DD speakerphone can be programmed to dial a PBX access number, allow or block incoming calls, and provide conversation time-out.	The SSP-511-D stainless steel, wall speakerphone with push button automatic dialer, can be programmed to dial a PBX access number, allow or block incoming calls, provide conversation time-out or no time-out. The SSP-511-D2 will dial a second number if called party doesn't answer. The SSP-511-X is for ring down circuits, inbound calls, and direct connect applications Includes wall mounting steel backplate and tamper resistant security hardware.
SSP-510-F	FD Low power not available	DD Low Power not available	SSP-510-D OR X
The SSP-510-F is a low power consumption speakerphone with keypad that does not have the additional smart features. Full function ADA features are not available on low power models.	SSP-511-FD Programmable speakerphone is not available in a low power version. Please see above.	SSP-511-DD Programmable speakerphone is not available in a low power version. Please see above.	The SSP-510-D OR X available in low power speakerphones. Full function ADA features are not available on low power models. The SSP-511-D2 telephone is not available in low power.
Dimensions: 7 1/6"W x 11 1/4"H x 4 1/4"D Weight: 6lbs	Dimensions: 7 1/6"W x 11 1/4"H x 4 1/4"D Weight: 6lbs	Dimensions: 7 1/6"W x 11 1/4"H x 4 1/4"D Weight: 6lbs	Dimensions: 7 1/6"W x 11 1/4"H x 4 1/4"D Weight: 6lbs

IP - Voice over Internet Protocol Version available on all models (SIP)

CUSTOMIZATION - Call us for additional options and features

Visit our website at www.ceeco.net or call us at 863-357-0798 for detail specifications on any of our models.



CEECO has been providing telecom solutions since 1930. Our vandal resistant technology focuses on providing public communication solutions while reducing replacement and repair costs, lowering the customer's total cost of ownership. CEECO also offers custom design and branding to your specifications. Our commitment to providing expert service and support extends beyond the warranty of our product. We offer support for the life of the product! CEECO is devoted to giving you the quality and service you deserve.

Providing Telecommunication Solutions Since 1930

Communication Equipment
& Engineering Company

Web: www.ceeco.net

Email: sales@ceeco.net

519 SW Park Street
Okeechobee, FL 34972

Voice 863-357-0798

Fax 863-357-0006