

# SERVICE MANUAL

FOR

**MODEL SSC-301-F**  
(FORMERLY 301-FS)

OR

**MODEL BLC-301-F**  
(FORMERLY 301-F)

**CHARGE-A-CALL TELEPHONE**



*Serving the Telephone Industry Since 1930*

---

*Communication Equipment  
& Engineering Company*

---

519 SW Park Street

---

Okeechobee, FL 34972

---

Voice: 863-357-0798

---

Fax: 863-357-0006

---

# IMPORTANT INFORMATION FOR CUSTOMER

Please fill in before you continue.

The following information is necessary when calling CEECO for assistance.

MODEL NUMBER	MODEL SSC-301-F OR BLC-301-F
SERIAL NUMBER	
DATE MANUFACTURED	
LOCATION INSTALLED	

For us to better serve you, please have this information available when calling for technical support.

## **CEECO** *Communication Equipment & Engineering Company*

519 SW Park Street  
Okeechobee, FL 34972

(863) 357-0798 Voice

(863) 357-0006 Fax

## TABLE OF CONTENTS

<b><u>SECTION</u></b>	<b><u>PAGE</u></b>
<b>1.0 INTRODUCTION.....</b>	<b>4</b>
<b>2.0 GENERAL DESCRIPTION.....</b>	<b>4</b>
<b>3.0 OPERATION .....</b>	<b>4</b>
<b>4.0 RECOMMENDED TOOLS AND TEST EQUIPMENT .....</b>	<b>4</b>
<b>5.0 INSTALLATION NOTES AND ASSEMBLY INSTRUCTIONS .....</b>	<b>5</b>
<b>6.0 TESTING.....</b>	<b>6</b>
<b>7.0 TROUBLE SHOOTING GUIDE .....</b>	<b>7</b>
<b>8.0 SPECIFICATIONS.....</b>	<b>8</b>
<b>9.0 PARTS LIST .....</b>	<b>9</b>
<b>10.0 FCC NOTICE.....</b>	<b>10</b>
<b>11.0 REPAIR AND RETURN INFORMATION.....</b>	<b>11</b>
<b>12.0 WARRANTY POLICY .....</b>	<b>12</b>

## 1.0 INTRODUCTION

The practices in this manual provide installation and maintenance information for Model SSC-301-F OR BLC-301-F (Formerly known as 301-F(S) ) Charge-A-Call Telephone.

The information in this manual is subject to change without notification.

For information not included in this manual, please call or write:

**CEECO**  
Customer Service  
519 SW Park Street  
Okeechobee, FL 34972

(863) 357-0798  
(863) 357-0006 FAX  
[sales@ceeco.net](mailto:sales@ceeco.net)

## 2.0 GENERAL DESCRIPTION

The CEECO model SSC-301-F OR BLC-301-F is a Charge-A-Call Telephone equipped with a metal button tone dial. The telephone is designed for special applications where a telephone must be both sturdy and attractive.

## 3.0 OPERATION

Lift the handset. After dial tone is heard dial your number using the keypad. Normal phone operation follows.

## 4.0 RECOMMENDED TOOLS AND TEST EQUIPMENT

Volt/Ohm Meter  
1/4" Nut Driver  
Flat Blade Screw Driver  
Security Tool CEECO Part Number 301-037

## 5.0 INSTALLATION NOTES AND ASSEMBLY INSTRUCTIONS

- 5.1 Using a 301-037 security tool (sold separately), loosen (**do not remove**) the security screw.
- 5.2 The security tool is for a standard 5/32" button head screw generally used on the framework of the phone booths.
- 5.3 Separate the cover assembly from the backplate assembly by pulling the bottom of the cover forward and pushing up. The backplate assembly is designed to be mounted on any flat vertical surface. Four mounting holes are provided.
- 5.4 Run the inside station wire through the backplate assembly and terminate the RJ11C terminal block located on the backplate.
- 5.5 The use of a gas tube station protector is recommended. The station ground should not exceed 50 ohms.
- 5.6 Install the instruction card kit using a 5/16" nut driver.
- 5.7 Plug the modular line cord from the cover assembly into the RJ11C terminal block.
- 5.8 Dress the line cable away from the security screw and install the cover assembly by placing the two tabs into the two corresponding slots. Secure the cover assembly by tightening the security screw.

### **\*\*\*\*\*WARNING\*\*\*\*\***

- A. **Never install telephone wiring during a lightning storm.**
- B. **Never install telephone jacks in wet locations unless the jack is specifically designed for wet locations.**
- C. **Never touch uninsulated telephone wires or terminals unless the telephone line has been disconnected at the network interface.**
- D. **Use caution when installing or modifying telephone lines.**

## **6.0 TESTING**

- 6.1** Connect the phone to a phone line or a DTMF phone test set.
- 6.2** Lift the handset, dial tone is heard.
- 6.3** Dial a number. (The transmitter is muted while the phone is dialing.)
- 6.4** Normal phone conversation is allowed. Place the handset on hook.
- 6.5** Place a call into the phone.
- 6.6** Normal phone conversation is allowed.

## 7.0 TROUBLE SHOOTING GUIDE

Always visually check the phone for loose or shorted wires, damaged terminals or damaged parts.

**PROBLEM:** NO DIAL TONE

**POSSIBLE CAUSE:**

LINE CORD  
RJ11C CONNECTOR  
NETWORK  
HANDSET  
DIAL PC BOARD

**PROBLEM:** DIAL TONE IS DISTORTED

**POSSIBLE CAUSE:**

NETWORK  
HANDSET  
DIAL PC BOARD

**PROBLEM:** TRANSMITTER DOES NOT TURN ON

**POSSIBLE CAUSE:**

HANDSET  
NETWORK  
DIAL PC BOARD

**PROBLEM:** PHONE DOES NOT DIAL

**POSSIBLE CAUSE:**

DIAL PC BOARD  
KEYPAD

**PROBLEM:** RINGER DOES NOT OPERATE

**POSSIBLE CAUSE:**

RINGER  
NETWORK

## 8.0 SPECIFICATIONS

INPUT POWER:	C.O. Line Powered
LOOP CURRENT:	23ma min to 80ma max
IMPEDANCE:	600 ohms
SIGNALING:	DTMF
HEARING AID COMPATIBLE:	Meets EIA standards
ENVIRONMENTAL:	Temperature 0°C to 50°C Humidity 20%-90%
TELEPHONE COVER:	14 gauge Steel, Zinc Chromate Plating, Blue Polyurethane Paint
DIMENSIONS:	7.5" Wide x 21" High x 6.5" Deep (Handset on hook)
MOUNTING:	Standard Coinless Public Telephone footprint
WEIGHT:	17 lb.
FCC REGISTRATION:	BW88T7-68413-TE-T
UL LISTED NO.:	6OF5
RINGER EQUIVALENCY:	0.4A
TYPE JACK:	RJ11C



## 9.0 PARTS LIST

<u>QUANTITY</u>	<u>PART NUMBER</u>	<u>DESCRIPTION</u>
1	301-021	Blue Charge-A-Call Cover <b>or</b>
1	301-231	Stainless Steel Cover
1	735-100	Model 730 Metal Button Tone Dial
1	301-004	Handset with Armored Cord
1	401-009	Ringer
1	301-009	Network
1	301-581	Tongue and Bracket Assembly
1	301-588	Hookswitch Cradle
2	301-570	Microswitch Assembly
1	301-018	Modular Cord
1	301-051	Backplate
1	301-012	Locking Rod Screw
2	321-016	1/4" x 20" x 3/4" Security Screw
1	308-016	Handset Swivel
1	301-052	Grommet
1	301-054	Modular Jack (UL)
1	301-030	Instruction Card Kit
1	301-039	Number Window

### ACCESSORIES:

1	301-037	Security Tool
---	---------	---------------

### OPTIONS

1	301-106-18 Prison	Armored Cord Handset
	<b>or</b>	with
1	301-106-29 Standard	Internal Steel Lanyard

## **10.0 FCC NOTICE**

### **10.1 FCC REGISTRATION AND REPAIR INFORMATION**

Your new telephone has been registered with the Federal Communication Commission (FCC) in accordance with Part 68. The FCC requires that you be advised of certain requirements involving the use of this telephone.

### **10.2 CONNECTION WITH THE NATIONWIDE TELEPHONE NETWORK**

The FCC requires that you connect this telephone to the Nationwide Telephone Network through a registered jack provided by the telephone company in your area. This jack is a modular outlet, which you can order from your local telephone company.

### **10.3 NOTIFICATION TO THE TELEPHONE COMPANY**

Before connecting this telephone, the FCC requires that you notify your local telephone company business office. The number is in the front of your phone book.

Tell them: The "line" to which you will connect the telephone (that is, your phone number) and the telephone's FCC registration number and ringer equivalence number. These numbers are listed in section 7.0.

The FCC further requires that you notify your local telephone company when permanently disconnecting this telephone.

## **11.0 REPAIR AND RETURN INFORMATION**

### **11.1 WARRANTY REPAIR**

Any device returned requiring warranty service, repair or credit must be accompanied with a "Return Material Authorization" (RMA) Form. It must include: RMA Number, return shipping instructions., original purchase order number, serial number and special marking instructions. A tag with the trouble observed must be attached to the defective unit. This information must be inside the shipping container.

### **11.2 DIRECT ALL INQUIRES TO:**

**CEECO**  
Repair Department  
519 SW Park Street  
Okeechobee, FL 34972

(863) 357-0798  
(863) 357-0006 FAX  
[sales@ceeco.net](mailto:sales@ceeco.net)

### **11.3 NON-WARRANTY REPAIR**

CEECO will repair equipment out of warranty for a set charge plus parts. The customer must pay the shipping costs both directions.

### **11.4 RETURN FOR CREDIT**

Material may be returned for credit only with prior approval. Material authorized for return is subject to a 15% restocking charge based on the manufacturer's list price. Return Material Authorization must be requested no later than 30 days after original shipment. Items returned for credit must be returned in their original shipping container.

## **12.0 WARRANTY POLICY**

### **12.1 GENERAL**

CEECO guarantees its products to be free from defects in material and workmanship for a period of 365 days from the date of original purchase. CEECO's obligation under this warranty is limited to repair or replacement of any part found to be defective by CEECO.

UNDER NO CIRCUMSTANCES shall CEECO be liable for loss, damage, cost of repair or consequential damages of any kind, which have been caused by neglect, abuse or improper operation of equipment.

CEECO will repair or replace any unit during this period if found to be defective for reasons other than abuse and improper use or improper installation. It is the buyer's responsibility to return the defective unit to the factory. CEECO will then repair or replace any defective parts and return them to the buyer free of charge.

### **12.2 PRINTED CIRCUIT BOARDS**

Printed circuit boards should not be repaired in the field. If a unit is found to be faulty, replace it with another unit and return the faulty unit to CEECO for repair. Modifications by any one other than CEECO will void the warranty.